

EnerCube

Containerized Battery Energy Storage System



The **3rd** generation modular containerized BESS

Design optimization cuts lead time by **1/2** (VS traditional BESS structure)

Complete IEC62619, IEC62477, IEC61000, EN50549, G99, UN3536, UN38.3, China Classification Society, etc.

DC BUS grid-forming (GFM) technology ensures **100%** availability of battery cluster capacity

Safe & Stable

Design patent of preventing flame outward expansion enhances product safety.

Economical & Efficient

Containerized design for easy transportation & installation reduces transportation and site construction costs.

Modular O&M

Modular O&M without interference in the normal operation of other modules for cost savings and utilization optimizing.

Flexible Expansion

Flexible configuration on demand; Modularized structure; Multiple cabinets parallel connection and control.



Industrial Park Energy Storage

Capacity Expansion
Peak-load Shifting
TOU Tariff Arbitrage
Power Quality Management



Solar + Storage + EV Charging Station

Store Extra Solar Energy
Peak-load Shifting
Electricity Cost Saving
Power Expansion for More Chargers
Eco-friendly Solution



Solar + Storage Microgrid

Backup Power
Store Extra Solar Energy
Distributed Energy Integration
Optimizing The Power Grid Upgrading

EnerCube

Containerized Battery Energy Storage System

Parameters	EnerCube P400C860	EnerCube P500C1075	EnerCube P600C1290	EnerCube P700C1505	EnerCube P800C1720
Battery Parameters					
Cell type & capacity	LFP-280Ah				
Battery module type	1P20S (P20)				
System configuration	4*1P240S	5*1P240S	6*1P240S	7*1P240S	8*1P240S
System capacity (BOL)	860kWh	1075kWh	1290kWh	1505kWh	1720kWh
AC Output Parameters					
Rated output power	400kW	500kW	600kW	700kW	800kW
Rated voltage	AC400V, 3P4W				
Rated grid frequency	50Hz±5Hz/60Hz±5Hz				
Maximum output current	577A	722A	866A	1010A	1155A
Harmonics	< 3% (@rated power)				
Overload capacity	110%, 10 mins; 120%, 60s				
General Parameters					
Isolation transformer	Optional				
Protection level	Outdoor installation (Battery cabinet: IP55, Electrical room: IP34)				
Container anti-corrosion grade	C3				
Operating temperature*	-20°C~55°C				
Relative humidity	0~95% (non-condensing)				
Permissible altitude**	2000m				
Cooling method	Battery cabinet: HVAC, Electrical room: forced air cooling				
Noise emission	≤75dB				
Dimension (W*D*H)	20HQ container (6058mm×2438mm×2896mm)				
Max. weight	25000kg				
Fire fighting system	FAS & FM200/Novac1230				
Communication interface and protocol	Ethernet, Modbus TCP/IP				
Warranty	5 years (can be extended to 10 years)				

* The system will be derated when the ambient temperature exceeds 45°C.

**The system will be derated when the altitude exceeds 2000m.



Global Headquarters: SHENZHEN PANDPOWER CO., LTD

Tel: +86 - 755 - 28836582

Email: official@pandpower.com

Version No.:1.1

Website: www.pandpower.com

Add: Factory 901, No.2, Baitai Gold Jewelry Building, No.1 Guangke 1st Road,

Laokeng Community, Longtian Street, Pingshan District, Shenzhen

PAND reserves the right of final interpretation of the above data and reserves the right to change the above data without prior notice.